

CE/ISO 9001 Belgeli Onaylı (Approval)

|                  |   |
|------------------|---|
| MODEL            | XFR 205 DR  |
| KAPASİTE         | 205 gr  |
| HASSASİYET       | 0,00001 gr / 0,0001 gr                              |
| DARA ALANI       | 92 / 205 gr   |
| DOĞRUSALLIK ±    | 0,00006 gr  |
| CEVAP SÜRESİ     | 10Sn  |
| EKRAN TİPİ       | LCD Liquid Crystal Display                          |
| EBAT W/D/H       | 210/340/345mm Net ağırlık 6,9 kg                    |
| KEFE YAPISI      | Cr-Ni Paslanmaz 80 mm dairesel                      |
| KALİBRASYON TİPİ | Tam Otomatik Zaman Ayarlı Dahili Kalibrasyon 230 mm |
| RÜZGARLIK        | 265 mm uzunlukta, Uc Yonden-İki islerli Kapaklı     |

|              |   |
|--------------|---|
| Model        | XFR 205 DR                                  |
| Capacity     | 205 gr                                      |
| Readibility  | 0,00001 gr / 0,0001 gr                      |
| Tare range   | 92 / 205 gr                                 |
| Linearity ±  | 0,00006 gr                                  |
| Aowertime    | 10Sn  |
| Screen type  | LCD Liquid Crystal Display                  |
| Size W/D/H   | 210/340/345mm Net ağırlık 6,9 kg            |
| Pan metarial | Cr-Ni stainless 80 mm dia.                  |
| Calibration  | Automatic time setable internal calibration |
| Windshield   | 265 mm lenght, Uc sliding door windshield   |

| Model      | Kapasite    | Hassasiyet          | Kefe Çapı |
|------------|-------------|---------------------|-----------|
| XFR 205 DR | 92 / 205 gr | 0.00001 / 0.0001 gr | 80 mm dia |
| Model      | Capacity    | Sensitivity         | Pan Size  |
| XFR 205 DR | 92 / 205 gr | 0.00001 / 0.0001 gr | 80 mm dia |

